

COPPER SYSTEM

Field installable RJ45 connector Cat. 6A Class EA

The field installable RJ45 connector Cat. 6A Class EA can be installed quickly and without tools. The connector is suitable for a wide range of cable diameters & AWG. Additionally, it has a solid strain relief and is suitable for PoE++.



Features

- quickly applicable without tools
- with separate dust cap and bend protection sleeve
- gold plated RJ45 plug
- suitable for wide range of cable diameters (5.0mm-8.5mm)
- suitable for wide range of AWG compatibility (22 AWG-27AWG)
- strain relief by solid metal cable gland

Standards

- IEC60603-7-5
- ANSI-TIA568.2-D MPTL
- Cat. 6A / Class EA MPTL
- PoE per IEEE 802.3af, , PoE+ per IEEE 802.3at, PoE++ per IEEE 802,3bt
- RoHS 2.0 & REACH



COPPER SYSTEM

Field installable RJ45 connector Cat. 6A Class EA

Specifications


mating cycles	≥750 times
contact resistance	≤20mΩ
insulation resistance	≥500mΩ
withstanding voltage	DC 1000V AC 700V RMS 60 Hz, 1Min
cable OD	5.0mm - 8.5mm
solid cable	1/22AWG(0.65MM) - 1/26AWG(0.4MM) ID:1.1MM - 1.6MM
stranded cable	7/24AWG(7/0.20mm) - 7/27AWG(7/0.14mm) ID:1.1MM - 1.6MM
housing material	Zinc alloy
RJ 45 plug	8P8C gold plated
PoE	PoE, PoE+, PoE++
operating temperature	-10°C to +60°C
storage temperature	-40°C to +70°C




COPPER SYSTEM

Field installable RJ45 connector Cat. 6A Class EA

Technical drawing







Order number: CD-RJ45M-C6A